



NVIDIA QUADRO FX 4800

NEW REALMS OF VISUAL COMPUTING



QUADRO FX 4800
DATASHEET

Whether designing and bringing the next luxury vehicle to market, creating the next blockbuster film or providing a diagnosis of a patient's condition, professionals push the boundaries of realism, performance and quality everyday.

In an increasingly competitive and high-pressure landscape, professionals need to deliver results better, faster, and more cost effectively than ever before and traditional processing paradigms just cannot keep up.

To get ahead of this trend, a new visual computing model is emerging based on the latest generation NVIDIA® Quadro® FX 4800 ultra-high-end graphics card. Professional applications take advantage of the Quadro FX 4800 graphics solution's advanced feature set, including 1.5 GB of graphics memory, and high color fidelity, providing the right set of tools to deliver results that push the realms of visual computing.

The Quadro FX 4800 is the second-generation NVIDIA GPU unified-architecture delivering up to 50% increased performance over the first generation through 192 processor cores. The entire Quadro family takes professional visualization applications to a new level of interactivity by enabling unprecedented programmability and precision. The industry's leading workstation applications leverage these

capabilities to deliver hardware-accelerated features, performance, and quality not found in other professional graphics solutions. From Quadro FX 5800, 5600, and 4800 at the ultra-high-end, and Quadro FX 4600 and 3700 at the high-end, through Quadro FX 1700 at the mid-range, to Quadro FX 570 and 370 at the entry-level, Quadro delivers the productivity you need at every price.

PRODUCT SPECIFICATIONS

- FORM FACTOR
 - > 4.36" H x 10.5" L
- FRAME BUFFER MEMORY
 - > 1.5 GB GDDR3
- MEMORY INTERFACE
 - > 384-bit
- MEMORY BANDWIDTH
 - > 76.8 GBps
- MAX POWER CONSUMPTION
 - > 150W
- GRAPHICS BUS
 - > PCI Express Gen 2 x16
- DISPLAY CONNECTORS*
 - > Single DVI-I, Dual Display Port, Stereo
- DUAL LINK DVI
 - > Yes (1)
- DISPLAY PORT
 - > Yes (2)
- AUXILIARY POWER CONNECTORS
 - > Yes (1)
- NUMBER OF SLOTS
 - > 2
- THERMAL SOLUTION
 - > Active Fansink
- G-SYNC
 - > Yes (Optional)
- SDI
 - > Yes (Optional)

* Only two (2) display connectors can be active at one time

FEATURES AND BENEFITS

1.5 GB GDDR3 GPU MEMORY WITH ULTRA FAST MEMORY BANDWIDTH	Massive 1.5 GB frame buffer and memory bandwidth up to 76.8 GBps delivers high throughput for interactive visualization of large models and high-performance for real time processing of large textures and frames and enables the highest quality and resolution full-scene antialiasing (FSAA).
NVIDIA® CUDA™ PARALLEL COMPUTING PROCESSOR	A parallel computing processor architecture exposed through a C language environment and tool suite in combination with high performance visualization, CUDA unleashes new capabilities to solve highly complex challenges such as real-time ray tracing, video encoding, and interactive volume rendering.
HIGHEST COLOR FIDELITY	10-bit per component color fidelity enables billions rather than millions of color variations for rich, vivid image quality with the broadest dynamic range.
DUAL DISPLAYPORT DIGITAL DISPLAY CONNECTORS	Dual DisplayPort connectors support ultra-high-resolution panels (up to 2560 x 1600)—which result in amazing image quality producing detailed photorealistic images.
SINGLE DUAL-LINK DIGITAL DISPLAY CONNECTORS	Dual-link TMDS transmitter supports ultra-high-resolution panels (up to 2560 x 1600 @ 60Hz)—which result in amazing image quality producing detailed photorealistic images.
QUAD BUFFERED STEREO	Offers enhanced visual experience for professional applications that demand stereo viewing capability.
NVIDIA® SLI® TECHNOLOGY	A revolutionary platform innovation that enables professional users to dynamically scale graphics performance, enhance image quality, and expand display real estate.

TECHNICAL SPECIFICATIONS

SUPPORTED PLATFORMS

- > Microsoft Windows Vista (64-bit and 32-bit)
- > Microsoft Windows XP (64-bit and 32-bit)
- > Microsoft Windows 2000 (32-bit)
- > Linux® - Full OpenGL implementation, complete with NVIDIA and ARB extensions (64-bit and 32-bit)
- > Solaris®
- > AMD64, Intel EM64T
- > PCI Express 2.0 Support

NVIDIA QUADRO FX 4800 ARCHITECTURE

- > 128-bit color precision
- > Unlimited fragment instruction
- > Unlimited vertex instruction
- > 3D volumetric texture support
- > Hardware-accelerated, antialiased points & lines
- > Hardware OpenGL overlay planes
- > Hardware-accelerated, two-sided lighting

- > Hardware-accelerated clipping planes
- > 3rd-generation occlusion culling
- > Window ID clipping functionality
- > Hardware-accelerated line stippling

SHADING ARCHITECTURE

- > Full Shader Model 4.0 (OpenGL 2.1/DirectX 10 class)
- > Long fragment programs (unlimited instructions)
- > Long vertex programs (unlimited instructions)
- > Looping and subroutines (up to 256 loops per vertex program)
- > Dynamic flow control
- > Conditional execution

HIGH LEVEL SHADER LANGUAGES

- > Optimized compiler for Cg and Microsoft HLSL
- > OpenGL 2.1 and DirectX 10 support
- > Open source compiler

HIGH-RESOLUTION ANTIALIASING

- > Rotated Grid Full-Scene Antialiasing (RG FSAA)
- > 32x FSAA dramatically reduces visual aliasing artifacts or “jaggies” at resolution up to 1920 x 1200
- > 64x FSAA SLI Mode

DISPLAY RESOLUTION SUPPORT

- > Dual DisplayPort support—ultra-high resolution panels (up to 2560 x 1600)
- > Single dual-link DVI-I output drives digital displays at resolutions up to 2560 x 1600 @ 60Hz
- > Internal 400 MHz DACs—Two analog displays up to 2048 x 1536 @ 85Hz

NVIEW ARCHITECTURE

- > Advanced multi-display desktop & application management, seamlessly integrated into Microsoft Windows

To learn more about NVIDIA Quadro, go to www.nvidia.com/quadro